

In th Claims:

1.(Canceled)

2.(Original) A method for displaying information concerning power consumption of an electronic device on a display, said electronic device having a display and driven by an AC adapter or a battery pack enabling the sending of information concerning power consumption, said method comprising the steps of:

stopping supply of electrical power for a predetermined time, when said AC adapter is supplying electrical power to said electronic device,
so as to supply said electric power to said electronic device from said battery pack;
obtaining information concerning a power consumption value from said battery pack; and,
displaying said information concerning the power consumption value.

3.(Original) The method according to Claim 2, comprising the further step of: processing said information concerning the power consumption value obtained from said battery pack prior to displaying said information on said display.

4. (Canceled)

5.(Original) An electronic device driven by a battery pack enabling the sending of information concerning power consumption, comprising:

a micro-controller for receiving information concerning a power consumption value from said battery pack and outputting said information concerning the power consumption value; and

a display for displaying information concerning the power consumption value output from said micro-controller.

6.(Original) The electronic device according to Claim 5, wherein said micro-controller processes information concerning the power consumption value received from said battery pack and outputs said processed information concerning the power consumption value.

7.(Original) An electronic device driven by an AC adapter or a battery pack enabling the sending of information concerning power consumption, comprising:

a controllable switch for shutting off electric power supplied from said AC adapter and selecting power supply from said battery pack for a predetermined time;

a micro-controller for outputting a control signal to said switch so as to shut off said electric power to said electronic device, and for receiving information concerning a power consumption value from said battery pack and outputting said information concerning power consumption; and

a display for displaying information concerning the power consumption value output from said micro-controller.

8.(Original) An electronic device driven by an AC adapter or a battery pack enabling the sending of information concerning power consumption, comprising:

a line for supplying electric power to said electronic device from said battery pack if said electric power from said AC adapter is shut off;

a communication controller for receiving information concerning a power

consumption value from said battery pack and outputting said information concerning power consumption if said line is used to supply said electric power; and a display for displaying information concerning the power consumption value output from said communication controller.

9.(Currently Amended) An electronic device driven by an AC adapter and a battery pack enabling the sending of information concerning power consumption, comprising:

a first input terminal connectable to said AC adapter;

a load terminal connectable to an electric power load of said electronic device;

a second input terminal connectable to an electric power terminal of said battery

pack;

a communication terminal connectable to a signal terminal of said battery pack;

a switch provided with a control terminal, its one terminal being connected to said first input terminal and its second terminal being connected to said load terminal;

a line for connecting said second input terminal to said load terminal;

a communication controller provided with an input terminal connected to said communication terminal and used to receive information concerning a power consumption value from said battery pack;

a control terminal connected to a the control terminal of said switch and used to turn off said switch for a predetermined time if said AC adapter supplies electric power to said first input terminal so as to send a control signal to said switch and let said battery pack supply said electric power; and

a terminal for receiving information concerning the power consumption value of said battery pack from said communication terminal while said switch is off and outputting said information concerning the power consumption value in the same format or in a different format; and

a display for displaying information concerning the power consumption value output

from said communication controller.

10.(New) An electronic device comprising:

a battery pack enabled to communicate information concerning power consumption;

a power supply having an AC adapter and said battery pack;

a line coupled to said electronic device for supplying electric power to said electronic device from said battery pack which supplies electric power when the AC power is lost;

a controllable switch for shutting off electric power supplied from the AC adapter and selecting power from said battery pack for a predetermined time;

a controller, coupled to said battery pack and said controllable switch, which disables said switch so as to shut off the power from the AC adapter to said electronic device and receives power consumption information from said battery pack, and outputs said information concerning power consumption if said line is used to supply electric power; and

a display, coupled to said communication controller, which displays power consumption information output from said controller in one of the formats selected from the group consisting of a line graph, a bar graph and value information.

11.(New) The electronic device according to Claim 10, wherein said controller reduces the frequency of collection of power consumption information when said electronic device is powered by said battery pack whereby unnecessary battery performance degradation is avoided solely due to the collection and display of power consumption data.

12.(New) The electronic device according to Claim 10, wherein said controller processes power consumption information received from said battery pack and outputs the

processed power consumption information.

13.(New) A method comprising the steps of:

controlling a switch coupled to an AC adapter;
disabling the switch to change an electronic device power source from an AC
adapter to a battery pack;
stopping supply of AC electrical power for a predetermined time, when said AC
adapter is supplying electrical power to the electronic device,
supplying electric power to the electronic device from said battery pack;
obtaining power consumption information value from the battery pack;
processing the power consumption information collected in said obtaining step;
displaying the power consumption information in one of the formats
selected from the group consisting of a line graph, a bar graph and value information.